
## Search through plan space

- Planning as a search through plan space
  - nodes represent partially specified plans
  - edges denote plan-refinement operations
- Facilitates thinking about alternative
  - representations of partially specified plans
  - plan-refinement operators
- Partial order plan representations
  - a plan is represented as a partially ordered sequence
  - planning algorithm practices least commitment


#### Partial order plans

- A plan is a three tuple  $\langle A, O, L \rangle$ 
  - A is the set of actions in the plan
    - initially we consider only ground actions
  - O is the set of ordering constraints among the actions
    - O must be consistent
  - L is the set of causal links



#### Causal links

- Records dependencies between actions
- A causal link consists of
  - the producer  $A_p$
  - the consumer  $A_c$
  - the proposition Q
- A causal link states that
  - action  $A_p$  has an effect Q
  - action  $A_c$  has a precondition Q
  - -Q will be made true for  $A_c$  by  $A_p$



#### **Threats**

- An action  $A_t$  is a *threat* to a causal link  $A_p \xrightarrow{Q} A_c$  in a plan  $\langle A, O, L \rangle$  if
  - $-O \quad \{A_p < A_t < A_c\}$  is consistent
  - $-A_t$  has  $\neg Q$  as an effect

## Resolving a threat

- Threats are resolved by adding additional ordering constraints
- Promotion
  - add the constraint  $A_c < A_t$
- Demotion
  - add the constraint  $A_t < A_p$

#### Representing null plans

#### Introduce two pseudo-actions

- *Start*: effects are the initial state and preconditions are empty
- End: preconditions are the goals and effects are empty
- Ordering constraint: *Start < End*

$$on A B \quad on B C$$
 $End$ 

## Partial order planning

```
algorithm POP(\langle A, O, L \rangle, Agenda)
   if Agenda is empty then return \langle A, O, L \rangle
   Remove some \langle Q, A_{need} \rangle from Agenda
   A_{add} = choose an action that can be ordered before A_{add}
       and has effect Q (an existing or newly instantiated action)
   if no such A_{add} exists then return "no plan"
   Add A_{add} \xrightarrow{Q} A_{need} to L and A_{add} < A_{need} to O
   if A_{add} is new then
       A = A {A_{add}}, add preconds(A_{add}) to Agenda and Start < A_{add} < End to O
   for every causal link A_p \xrightarrow{R} A_c threatened by some A_t do
       choose either to demote A_t or to promote A_t consistently
       if neither ordering is consistent then return "no plan"
   endfor
   POP(\langle A, O, L \rangle, Agenda)
end POP
```

# Example

Start

on CA clear B clear C on A Table on B Table

on A B on B C End

# A complete plan

• Figure 10 from Weld 1994

## Lifting

- Use *least-commitment* in operator instantiation
- An effect can support a precondition if the two *unify* 
  - add co-designation constraints resulting from the most general unifier of the effect and precondition
  - instantiate an operator by creating a copy with a fresh set of variables
- Operator preconditions can be non-codesignation constraints
- Threats need be resolved only when they are forced
  - means that a plan is complete only when all variables are instantiated
  - ensure by requiring that variables in preconditions and effects are the same and initial state has no variables

#### Lifted POP

```
algorithm LPOP(\langle A, O, L, | B \rangle, Agenda)
    if Agenda is empty then return \langle A, O, L \rangle
    Remove some \langle Q, A_{need} \rangle from Agenda
    A_{add} = choose an action that can be ordered before A_{add}
        and has an effect that consistently unifies with Q (existing or new action)
    if no such A_{add} exists then return "no plan"
    Add A_{add} \stackrel{\vee}{\to} A_{need} to L, A_{add} < A_{need} to O, and codesignation constraints from
        unification to B
    if A_{add} is new then
        A = A \{A_{add}\} and Start < A_{add} < End to O
        Add noncodesignation preconds of A_{add} to B and logical ones to A_{genda}
    endif
   for every causal link A_p \xrightarrow{R} A_c threatened by some A_t do
        choose either to demote A_t or to promote A_t consistently
        if neither ordering is consistent then return "no plan"
    endfor
    LPOP(\langle A, O, L, \overline{B} \rangle, Agenda)
end LPOP
```

#### **UCPOP**

- Augments the basic STRIPS operator representation with
  - conditional effects
  - disjunctive preconditions
  - universal quantification